

ST. CROIX MULTI-FUEL INSERT AND STOVE SPECIFICATIONS

ASHBY-MF



LINCOLN



GREENFIELD



AUBURN



LANCASTER



	ASHBY-MF	LINCOLN	GREENFIELD	AUBURN	LANCASTER
Width	45" (with std. surround)	25"	25"	24 ¾"	20"
Height	32" (with surround)	31"	32 ½"	34"	28 ½" (37 ¾" with legs)
Depth	24"	23"	23 ½"	26"	18"
Vent Size	3" rear vent	4" rear vent	3" rear vent	3" rear vent	3" rear vent
Minimum Fireplace Opening (Width)	24"	—	—	—	—
Minimum Fireplace Opening (Height)	20 ¾"	—	—	—	—
Minimum Fireplace Opening (Depth)	16"	—	—	—	—
Heating Capacity ¹	up to 1,800 sq. ft.	up to 2,100 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.
Hopper Capacity ²	60 lbs.	60 lbs. ³	50 lbs.	90 lbs.	35 lbs. (70 lbs. optional)
Burn Rate ⁴ (lbs./hr.)	1.25-4.5	1.7-6.0	1.25-4.5	1.25-4.5	1.25-4.5
BTUH ⁴	Up to 40,000	Up to 50,000	Up to 40,000	Up to 40,000	Up to 40,000
Ash Drawer	Yes	Yes	Yes	Yes	Yes
Electronic Ignition	No	Yes	No	No	No
Digital Controls	Yes	Yes	Yes	Yes	Yes
Room Thermostat	Optional	Optional	Optional	Optional	Optional
Shipping Weight	267 lbs.	385 lbs.	427 lbs.	285 lbs.	240 lbs.

¹Heating capacity will vary with home construction and climate.

²Hopper capacities will vary depending on the weight and volume of the fuel.

³The Lincoln has two hoppers—the standard 60 lb. hopper and a smaller 8 lb. hopper that feeds into the electronic ignition.

⁴Burn rate and BTUH will vary with fuel.

Safety test statement tested per: ASTM/E1509 ULL1482,
CAN/ULC 5627 B 366.2M/APFI/ASTM/E1509
Oregon Administrative Rules: 814-23-900 thru 814-23-909
Power requirements: 120 Volts AC (200-250 watts)



Products, specifications and prices subject to change without notice. Consult our Owner's Manuals for all final dimensions. St. Croix products are manufactured in the U.S.A.