

ST. CROIX PELLET INSERT AND STOVE SPECIFICATIONS

PRESCOTT EXL



PRESCOTT EXP



HASTINGS



AFTON BAY



YORK



Width	24 ¾"	24 ¾"	25"	25"	45" (with std. surround)
Height	31 ¾"	34"	32 ½"	31"	32" (with surround)
Depth	26"	26"	23 ½"	23"	24 ½"
Vent Size	3" rear vent	3" rear vent	3" rear vent	3" rear vent	3" rear vent
Minimum Fireplace Opening (Width)	—	—	—	—	24"
Minimum Fireplace Opening (Height)	—	—	—	—	19"
Minimum Fireplace Opening (Depth)	—	—	—	—	16"
Heating Capacity ¹	up to 1,800 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.	up to 1,800 sq. ft.
Hopper Capacity ²	75 lbs.	75 lbs.	40 lbs.	65 lbs.	40 lbs.
Burn Rate ³ (lbs./hr.)	1.2-4.5	1.2-4.5	1.2-4.5	1.2-4.5	1.2-4.5
BTUH ³	Up to 40,000	Up to 40,000	Up to 35,000	Up to 40,000	Up to 40,000
Ash Drawer	Yes	Yes	Yes	Yes	Yes
Electronic Ignition	Yes	Yes	Yes	Yes	Yes
Digital Controls	Yes	Yes	Yes	Yes	Yes
Room Thermostat	Yes	Yes	Yes	Yes	Yes
Shipping Weight	285 lbs.	299 lbs.	427 lbs.	285 lbs.	220 lbs.

¹Heating capacity will vary with home construction and climate.

²Hopper capacities will vary depending on the weight and volume of the fuel.

³Burn rate and BTUH will vary with fuel.

Safety test statement tested per: ASTM/E1509 UL1482,
CAN/ULC 5627 B 366.2M/APFI/ASTM/E1509
Oregon Administrative Rules: 814-23-900 thru 814-23-909
Power requirements: 120 Volts AC (Ignition: 400-500 watts,
Steady State: 200-250 watts)



Products, specifications and prices subject to change without notice. Consult our Owner's Manuals for all final dimensions. St. Croix products are manufactured in the U.S.A.



1919 Highway 34
Waco, NE 68460

www.stcroixstoves.com

